



STINGRAY

Best Performance for Library and Rental Applications

SMARTRAC STINGRAY inlays and tags featuring NXP ICODE SLIX and SLIX2 ICs are designed for all disc types: CD, DVD and Blu-ray. They provide best-in-class performance and robust readability for library and rental applications.

STINGRAY products, delivered in wet format, have strong adhesive properties, are reliable and have long lifetime in library and rental performance.

STINGRAY with NXP ICODE SLIX provides 896 bits of user memory, while NXP ICODE SLIX2 boasts an extended user memory of 2,528 bits. The tag provides excellent and cost effective security performance products for disc media, including self-check multi-read and improved gate EAS.

SMARTRAC's inlays and tags are compliant with ISO 9001:2015 Quality Management and ISO 14001:2015 Environmental Management. This ensures a reliable and state-of-the-art product that meets a variety of application needs, where high performance is a critical parameter.

Overview

Operating Frequency

13.56 MHz

Integrated Circuit (IC)

NXP ICODE SLIX & SLIX2

Antenna & Die-cut Size

Ø 105 mm / 4.13"

Ø 108 mm / 4.25"

International Standards

- ▶ ISO 15693
- ▶ ISO 18000-3 Mode 1
- ▶ NFC Forum Type 5


Application Areas

- ▶ Media & Document Management

STINGRAY

Best Performance for Library and Rental Applications

Technical Features			
IC + Memory NXP ICODE SLIX 896 bit	Size Ø 108 mm / 4.25 in	Format wet	Sales Code 3002067
NXP ICODE SLIX2 2,528 bit	Ø 108 mm / 4.25 in	wet	3006211
Operating Temperature	-40°C to 85°C / -40°F to 185°F		
Bending Diameter (D)	> 50 mm, tension max. 10 N		
Adhesive	Permanent pressure sensitive adhesive; usage temperature: min. -10°C to 90°C / min. 14°F to 194°F		
Shelf Life	+20 °C, 50 % RH / 68 °F, 50 % RH - minimum 2 years from the date of manufacturing		



SMARTRAC TECHNOLOGY GROUP uses three different qualification methods to evaluate the quality and reliability of RFID inlay and tag products. Products are tested according to IEC 60068-2-67 (temperature and humidity), JESD22-A104-B (temperature cycling) and an in-house developed bending test. All the graphs are indicative: performance in real life applications may vary.

SMARTRAC N.V. · Strawinskylaan 851 · 1077 XX Amsterdam · The Netherlands
Phone: +31 20 30 50 150 · Fax: +31 20 30 50 155 · info@smartrac-group.com

Contact: Sales & Customer Service
www.smartrac-group.com/contact

© 2017 SMARTRAC N.V.

All rights reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use.

